



PROLONGADOR ELÉCTRICO SUEM



Potencia máx.	Clavija y base	Cable
250 V · 16 A · 3680 W	2P + T	H05VV-F 3G 1,5 · 10 m
250 V · 16 A · 3680 W	2P + T	H05VV-F 3G 1,5 · 15 m
250 V · 16 A · 3680 W	2P + T	H05VV-F 3G 1,5 · 25 m

ENROLLADOR ELÉCTRICO SUEM



Potencia máx.	Bases	Cable
230 V · 14 A · 3200 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 5 m
230 V · 14 A · 3200 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 10 m
230 V · 14 A · 3200 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 15 m

POTENCIA: 3200 W DESENCROLLADO · 1100 W ENROLLADO



ENROLLACABLES IP20 · 3000 W



Potencia máx.	Bases	Cable	Ø carrete
230 V · 13 A · 3000 W	Base aérea con termostato	H05VV-F 3G 1,5 · 25 m	240 mm

ENROLLACABLES IP20 · 3500 W



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 3500 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 25 m	255 mm
230 V · 13 A · 3000 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 50 m	255 mm

ENROLLACABLES IP20 · 4000 W



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 4000 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 15 m	210 mm
250 V · 16 A · 4000 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 20 m	210 mm
250 V · 16 A · 4000 W	4 (2P + T) con termostato	H05VV-F 3G 1,5 · 50 m	270 mm



ENROLLACABLES IP44 · 3000 W



Potencia máx.	Bases	Cable	Ø carrete
230 V · 13 A · 3000 W	4 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 25 m	270 mm
230 V · 13 A · 3000 W	4 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 50 m	270 mm

ENROLLACABLES IP44 · 7000 W



Potencia máx.	Bases	Cable	Ø carrete
380 V · 16 A · 7000 W	4 (3P + T) con termostato y tapa	H05VV-F 4G 1,5 · 25 m	255 mm
380 V · 16 A · 7000 W	4 (3P + T) con termostato y tapa	H05VV-F 4G 1,5 · 40 m	310 mm



ENROLLACABLES IP55 · 3000-3600 W



IP55 · TERMOSTATO · TOMAS CON TAPA

Potencia máx.	Bases	Cable	Ø carrete
230 V · 16 A · 3000 W	3 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 25 m	270 mm
230 V · 16 A · 3600 W	3 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 25 m	270 mm
230 V · 16 A · 3000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 25 m	240 mm
230 V · 16 A · 3000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 50 m	300 mm



ENROLLACABLES IP55 · 3500 W



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 3500 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 25 m	290 mm
250 V · 16 A · 3500 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 1,5 · 50 m	290 mm

ENROLLACABLES IP55 · 3500 W METÁLICO



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 3500 W	3 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 25 m	255 mm
250 V · 16 A · 3500 W	3 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 50 m	310 mm



ENROLLACABLES IP55 4000 W · MODELO AZUL



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 4000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 2,5 · 25 m	255 mm
250 V · 16 A · 4000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 2,5 · 50 m	310 mm

ENROLLACABLES IP55 4000 W · MODELO GRIS



Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 4000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 2,5 · 25 m	255 mm
250 V · 16 A · 4000 W	3 (2P + T) con termostato y tapa	H05VV-F 3G 2,5 · 50 m	310 mm



ENROLLACABLES IP67 · 3500 W



PROTECCIÓN IP67
CABLE DE NEOPRENO · 25 M / 50 M

Potencia máx.	Bases	Cable	Ø carrete
250 V · 16 A · 3500 W	2 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 25 m · neopreno	255 mm
250 V · 16 A · 3500 W	2 (2P + T) con termostato y tapa	H07VV-F 3G 1,5 · 50 m · neopreno	310 mm